



RN7AS Antifreeze Tower

GENER WIND MACHINE - VOLVO V1F

OPTIMAL PROTECTION AREA > UP TO **7.5** HECTARES

✦ **FOLDING TOWER > GENER WIND MACHINE**

LENGTH / DIAMETER	10.50 metres / Ø 51 cm
WEIGHT	1300 Kg
MATERIAL	8 mm Galvanised Steel
VIBRATION SENSOR	Integrated
ANEMOMETER	Standard > Better protection against wind gusts
SOLAR PANEL	Standard > For maintenance purposes, recharge the battery when the panel is not used
ACCESS	Trap doors for transmission maintenance
DECCELERATORS	SUPERIOR: rotation completes in 4m30s INFERIOR: centrifuge clutch - 10-inch diameter
* WARRANTY	10 years (except for the clutch)



10 year*
WARRANTY




✦ **TWO-BLADE PROPELLER > GENER WIND MACHINE**

MATERIAL	Composite fibreglass materials
MODELLING	In a 3D virtual environment
STABILITY	Dynamic balance for oscillations
PROPELLER LENGTH	6 metres
ROTATIONAL SPEED	585 rot/min

✦ **ENGINE > VOLVO PENTA TAD541-VE**

ENGINE	4 cylinders - 5.0 litres / electronic control / Liquid cooling
INJECTION	Direct Injection - Diesel Common Rail
TORQUE	810 Nm / 1800-2200 rotations per minute
POWER	constant: V1F > 175 HP (129 KW)
CONSUMPTION	26 l/h
COUNTRY OF ORIGIN	Made in France, Lyon



2 year
WARRANTY

✦ **OPERATION SYSTEM > DEEPSEA**

START / STOP	Automatic / The user adjusts the starting temperature
LCD screen	Parameter control while the engine is running User interface in French
TEMPERATURE SENSORS	Lower , at the ground level + Upper , in the upper part of the tower
TRACING / CONTROL	Remote diagnosis via smartphone or PC (SIM card subscription)



WWW.WIND-MACHINE.COM